

Seitenkanal - Verdichter				Druckbetrieb 50 Hz 2900 min ⁻¹																								FU-Tabellen auf Anfrage																									
Δp mbar	0	25		50		75		100		125		150		175		200		225		250		275		300		325		350		375		400		425		450		475		500		550		600		650		Δp max					
RIC	m³/h	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	m³/h	kW	mbar	RIC						
RIC M 30 S	74	65	0,37	56	0,37	47	0,37	38	0,37	30	0,37	21	0,55																																	150	RIC M 30 S						
RIC M 40 S	137	127	0,75	117	0,75	107	0,75	96	0,75	86	0,75	76	1,1	66	1,1	55	1,1	45	1,5	35	1,5																											250	RIC M 40 S				
RIC M 50 S	219	206	1,1	193	1,1	179	1,1	166	1,1	153	1,1	140	1,5	126	1,5	113	2,2	100	2,2	86	2,2	73	3,0	60	3,0																									300	RIC M 50 S		
RIC M 60 S	304	288	2,2	273	2,2	257	2,2	242	2,2	227	2,2	211	2,2	196	2,2	181	3,0	165	3,0	150	4,0	135	4,0	119	4,0	104	4,0																							325	RIC M 60 S		
RIC M 70 S	414	394	2,2	374	2,2	354	2,2	334	2,2	314	2,2	294	3,0	274	3,0	255	3,0	235	4,0	215	4,0	195	5,5	175	5,5	155	5,5	135	5,5																					350	RIC M 70 S		
RIC M 70 ES	429	409	2,2	390	2,2	371	2,2	353	2,2	335	3,0	317	3,0	299	3,0	282	4,0	266	4,0	249	4,0	233	5,5	217	5,5	202	5,5	187	5,5																					350	RIC M 70 ES		
RIC M 75 S	477	454	4,0	431	4,0	408	4,0	384	4,0	361	4,0	338	4,0	315	5,5	292	5,5	268	5,5	245	5,5	222	7,5	199	7,5	176	7,5																							325	RIC M 75 S		
RIC M 80 S	536	514	3,0	493	3,0	471	3,0	450	3,0	428	3,0	406	4,0	385	4,0	363	5,5	341	5,5	320	5,5	298	7,5	276	7,5	255	7,5	233	7,5	211	9,2	190	9,2	168	9,2															425	RIC M 80 S		
RIC M 80 ES	561	540	3,0	519	3,0	499	3,0	478	3,0	458	4,0	438	4,0	418	4,0	399	5,5	379	5,5	360	5,5	341	7,5	322	7,5	303	7,5	284	7,5	266	9,2	248	9,2	230	9,2															425	RIC M 80 ES		
RIC M 90 S	663	639	4,0	616	4,0	593	4,0	570	4,0	546	4,0	523	5,5	500	5,5	477	5,5	453	7,5	430	7,5	407	7,5	384	9,2	360	9,2	337	9,2	314	11,0	291	11,0	268	11,0															425	RIC M 90 S		
RIC M 100 S	782	758	5,5	733	5,5	708	5,5	684	5,5	659	5,5	635	5,5	610	7,5	586	7,5	561	7,5	537	9,2	512	9,2	487	9,2	463	11,0	438	11,0	414	15,0	389	15,0	365	15,0															425	RIC M 100 S		
RIC M 110 S	915	889	7,5	863	7,5	837	7,5	812	7,5	786	7,5	760	7,5	734	7,5	708	9,2	682	9,2	656	11,0	630	11,0	605	11,0	579	15,0	553	15,0	527	15,0	501	15,0	475	18,5	449	18,5														450	RIC M 110 S	
RIC M 110 ES	944	930	7,5	895	7,5	871	7,5	847	7,5	823	7,5	799	7,5	775	7,5	752	9,2	729	9,2	706	11,0	683	11,0	660	11,0	638	15,0	615	15,0	593	15,0	571	15,0	550	15,0	528	18,5														450	RIC M 110 ES	
RIC M 120 S	1022	995	9,2	967	9,2	940	9,2	912	9,2	885	9,2	857	9,2	830	11,0	802	11,0	775	15,0	747	15,0	720	15,0	692	18,5	665	18,5	638	18,5	610	18,5	583	18,5																	400	RIC M 120 S		
RIC T 50-66 S	334	324	4,0	315	4,0	301	4,0	285	4,0	268	4,0	248	4,0	224	4,0	198	4,0	168	4,0																																225	RIC T 50-66 S	
RIC T 50 S	408	384	3,0	359	2,2	334	2,2	309	2,2	285	3,0	260	3,0	235	3,0	210	4,0	185	4,0	160	4,0																														250	RIC T 50 S	
RIC T 60 S	562	535	4,0	507	4,0	479	4,0	451	4,0	43	4,0	395	5,5	368	5,5	340	5,5	312	7,5	284	7,5	256		229	7,5																										300	RIC T 60 S	
RIC T 70 S	827	787	5,5	747	5,5	707	5,5	668	5,5	628	5,5	588	5,5	548	7,5	509	7,5	469	7,5	429	9,2	389	9,2	350	11,0	310	11,0																									325	RIC T 70 S
RIC T 70 ES	830	790	5,5	750	5,5	711	5,5	672	5,5	633	5,5	595	5,5	557	7,5	520	7,5	483	7,5	446	9,2	410	9,2	374	11,0	339	11,0																									325	RIC T 70 ES
RIC T 80 S	1006	967	7,5	928	7,5	890	7,5	851	7,5	812	7,5	773	9,2	734	9,2	695	11,0	656	11,0	617	11,0																															250	RIC T 80 S
RIC T 80 ES	1012	985	7,5	957	7,5	929	7,5	901	7,5	872	7,5	843	9,2	813	9,2	784	11,0	754	11,0	723	11,0	692	15,0	661	15,0	630	15,0	598	18,5	566	18,5																				375	RIC T 80 ES	
RIC T 90 S	1325	1278	11,0	1232	11,0	1185	11,0	1139	11,0	1092	11,0	1046	11,0	999	11,0	953	15,0	906																																			